



FEATURES

- Support 8 HDMI channels input
- Support H.264/AVC video encoding
- Support MPEG1 Layer 2 audio encoding
- Support PSI/SI editing and inserting
- Support VBR/CBR video bitrate mode
- Support 720P, 1080I, 1080P HD video format
- Support MPTS or 8 SPTS output

SPECIFICATIONS

Input	8xHDMI inputs
Video	
Resolution	1920x1080_60P, 1280x720_60P, 1920x1080_50P, 1280x720_50P 1920x1080_60i, 720x576_50i, 1920x1080_50i 720x480_60i
Encoding	MPEG-4 AVC/H.264
Rate Control	CBR/VBR
GOP Structure	IBBP
Advanced Pre.	De-interlacing, Noise Reduction, Sharpening
Audio	
Encoding	MPEG-1 Layer 2 (HE-AAC V2, LC- AAC Option)
Sampling rate	48KHz
Resolution	24-bit
Bit-rate	64Kbps~384Kbps each channel

Stream Output	MPTS and 8 SPTS over UDP, 1000 Base-T Ethernet interface
System function	Control interface LCD/keyboard operating, net manager (SNMP) Ethernet software & hardware upgrade
Miscellaneous	
Dimension (WxLxH)	440mmx410mmx44.5mm
Approx weight	0,5 kg
Temperature	0~45°C(work), -20~80°CStorage°C
Power	AC 100V-220V±10%, 50/60Hz
Consumption	25W