

PRMSAT-14A / 4 Way Splitter



Features

- Frequency range: 5-2150MHz
- Integrated separated diodes (EAC 08/09)
- Suitable for district supply 24 V, 0.5 A (Master)
- Connections: F-type connector
- Connection for potential balancing
- Small dimensions compact design
- EN 60728-11 and EN 50083-2: Suitability

Technical Data

	Mhz	4-Way Splitter
Transmission losses Input/Output (Db) :	10-70 MHz 70-770 MHz 770-1336 MHz 1336-2150 MHz 2150-2610 MHz	< 8.0 < 8.2 < 9.0 < 11.0 < 11.5
Isolation Input/Output (dB):	10-70 MHz 70-770 MHz 770-1336 MHz 1336-2150 MHz 2150-2610 MHz	> 16 > 20 > 20 > 17 > 17
Return Losses (dB):	10-70 MHz 70-770 MHz 770-1336 MHz 1336-2150 MHz 2150-2610 MHz	< 2.9 < 2.0 < 1.95 < 1.80 < 1.70
Connector	F plug-in slot	5 pieces (1 pcs input, 4x pcs. Output)
Dimensions:	(Width x Height x Depth) : 78x 50 x 28 mm	
Packaging Details:	Sales unit: 10 pcs Shipping unit 100 pcs. Package Volume shipping unit: 0.2 dm Gross weight shipping unit: 0.08 kg	