



Features

- Connector type; 75Ω
- Smart Design
- High Quality Material
- RG6 (for cable)

Technical Specifications

Frequency Range	0.3 - 3000MHz	
Impedance(Nom.)	75Ω	
Amp. Rating	5A	
Shielding Effectiveness	> 115 dB @ 1GHz	
Return Loss	(IEC 169.1.1)+	
(RF Analyzer E8357A)	5-480 MHz	43.8 dB
	480-750 MHz	40.0 dB
	750-1000 MHz	39.6 dB
	1000-1750 MHz	36.4 dB
	1750-2200 MHz	34.1 dB
	2200-3000 MHz	30.0 dB
Insertion Loss Max.	5-480 MHz	<0.01 dB
	480-750 MHz	<0.01 dB
	750-1000 MHz	<0.01 dB
	1000-1750 MHz	<0.01 dB
	1750-2200 MHz	<0.01 dB
	2200-3000 MHz	<0.01 dB
Temperature Installing	Installing	-5° to + 50°C
	Operating	-40° to + 100°C
	Storing	-40° to + 100°C
	Resistance Max. @1A DC	<1mΩ
	Body Parts / Inner Conductor	Brass CuZn 39Pb3
Plating	Body Parts / Inner Conductor	Nitin
	Insulators	POM/NATURAL
	O-Ring	EPDM
	Color	Black